

# ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025 / ISO 21930

Notor 36 Recessed (1200 mm)

**Fagerhults Belysning AB**



**EPD HUB, HUB-1481**

Published on 30.05.2024, last updated on 30.05.2024, valid until 30.05.2029

## GENERAL INFORMATION

### MANUFACTURER

|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | Fagerhults Belysning AB       |
| Address         | Åvägen 1, 566 80 Habo, Sweden |
| Contact details | info@fagerhult.se             |
| Website         | www.fagerhult.com             |

### EPD STANDARDS, SCOPE AND VERIFICATION

|                    |  |
|--------------------|--|
| Program operator   | EPD Hub, hub@epdhub.com  |
| Reference standard | EN 15804+A2:2019 and ISO 14025   |
| PCR                | EPD Hub Core PCR version 1.1, 5 Dec 2023   |
| Sector             | Construction product   |
| Category of EPD    | Third party verified EPD   |
| Parent EPD number  |  |
| Scope of the EPD   | Cradle to gate with options, A4-A5, B6 and modules C1-C4, D  |
| EPD author         | Josefin Carlsson   |
| EPD verification   | Independent verification of this EPD and data, according to ISO 14025:<br><input type="checkbox"/> Internal verification <input checked="" type="checkbox"/> External verification |
| EPD verifier       | Imane Uald lamkaddam, as an authorized verifier acting for EPD Hub Limited   |

The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

### PRODUCT

|                                   |                             |
|-----------------------------------|-----------------------------|
| Product name                      | Notor 36 Recessed (1200 mm) |
| Additional labels                 | -                           |
| Product reference                 | -                           |
| Place of production               | Habo, Sweden                |
| Period for data                   | 2023                        |
| Averaging in EPD                  | Multiple products           |
| Variation in GWP-fossil for A1-A3 | -6 % / +2 %                 |

### ENVIRONMENTAL DATA SUMMARY

|  |                                       |
|--|---------------------------------------|
| Declared unit                                | 1 unit of Notor 36 Recessed (1200 mm) |
| Declared unit mass                           | 2 kg                                  |
| GWP-fossil, A1-A3 (kgCO <sub>2</sub> e)      | 21,4                                  |
| GWP-total, A1-A3 (kgCO <sub>2</sub> e)       | 21,3                                  |
| Secondary material, inputs (%)               | 83,7                                  |
| Secondary material, outputs (%)              | 92,6                                  |
| Total energy use, A1-A3 (kWh)                | 120                                   |
| Net fresh water use, A1-A3 (m <sup>3</sup> ) | 0,65                                  |

## PRODUCT AND MANUFACTURER

### ABOUT THE MANUFACTURER

Fagerhult creates premium lighting solutions that enhance human well-being in professional and public environments. With sustainability and connectivity at heart, we focus on office, education, healthcare, retail and outdoor applications. We work closely with customers and partners in the European market and provide lighting solutions globally – with tailor-made solutions for our customers. The Fagerhult brand includes both the product company Fagerhults Belysning AB and 13 sales companies located around Europe.

### PRODUCT DESCRIPTION

A recessed luminaire for installation in suspended ceilings that works great for both for workplaces and creative surfaces. The compact size contributes to minimized use of materials in the product, whilst does not compromise on functionality and light treatment. An obvious choice when you want light as a part of the interior and the architecture, due to its opportunity to create symmetry and unique appearance. For installation in suspended ceilings with visible T-bars, VTB (24 mm) or one-piece suspended ceilings. Available in both single version and for systems with Beta Opti and Opal louvre.

### PRODUCT RAW MATERIAL MAIN COMPOSITION

| Raw material category | Amount, mass- % | Material origin   |
|-----------------------|-----------------|-------------------|
| Metals                | 82              | Global, mainly EU |
| Minerals              | 0               | -                 |
| Fossil materials      | 18              | Global, mainly EU |
| Bio-based materials   | 0               | -                 |

### BIOGENIC CARBON CONTENT

Product's biogenic carbon content at the factory gate.

|  |        |
|--|--------|
| Biogenic carbon content in product, kg C   | -      |
| Biogenic carbon content in packaging, kg C | 0,1197 |

### FUNCTIONAL UNIT AND SERVICE LIFE

|                        |                                       |
|------------------------|---------------------------------------|
| Declared unit          | 1 unit of Notor 36 Recessed (1200 mm) |
| Mass per declared unit | 2 kg                                  |
| Functional unit        | -                                     |
| Reference service life | 20 years                              |

### SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).

# PRODUCT LIFE-CYCLE

## SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

| Product stage |           |               | Assem-<br>bly stage |          | Use stage |             |        |             |               |                        |                       | End of life stage |           |                  |          | Beyond the<br>system<br>boundaries |          |           |
|---------------|-----------|---------------|---------------------|----------|-----------|-------------|--------|-------------|---------------|------------------------|-----------------------|-------------------|-----------|------------------|----------|------------------------------------|----------|-----------|
| A1            | A2        | A3            | A4                  | A5       | B1        | B2          | B3     | B4          | B5            | B6                     | B7                    | C1                | C2        | C3               | C4       | D                                  |          |           |
| x             | x         | x             | x                   | x        | MNR       | MNR         | MNR    | MNR         | MNR           | x                      | MNR                   | x                 | x         | x                | x        |                                    |          | x         |
| Raw materials | Transport | Manufacturing | Transport           | Assembly | Use       | Maintenance | Repair | Replacement | Refurbishment | Operational energy use | Operational water use | Deconstr./demol.  | Transport | Waste processing | Disposal | Reuse                              | Recovery | Recycling |

Modules not declared = MND. Modules not relevant = MNR.

## MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production as well as packaging materials and other ancillary materials. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.

The product contains components made of metals, plastics and electronics. Materials for the driver are included, as a part of the luminaire. All materials and components are transported to Fagerhult's production facility in Habo, Sweden, where the product is being assembled and packaged. Production losses of components that are either designed inhouse or contributes to a significant share of the product's mass are considered in the study. Electricity and district heating is needed for the manufacturing and assembling processes. The energy supply at Fagerhult's facility in Habo is 100 % renewable. Ancillary materials needed within the manufacturing and assembly process are considered neglected. The

product is packaged in a cardboard box. The product is being sent to the installation site on a wooden pallet wrapped in plastic film.

## TRANSPORT AND INSTALLATION (A4-A5)

Transportation impacts occurred from final products delivery to construction site (A4) cover fuel direct exhaust emissions, environmental impacts of fuel production, as well as related infrastructure emissions.

The transportation distance from production facility in Habo to the installation site is assumed as an average distance to existing markets based on market share. The calculated average transportation distance is 400 km for road transportation and 4 km for sea transportation based on the sales per market. Vehicle capacity utilization factor may vary in reality, but as the emissions caused by transports are relatively small in relation to the total results, the variety in load is assumed to be neglected and full load is assumed. Return trip is assumed to be used by the transportation company to serve the needs of other clients, therefore are empty returns not taken into account. Transportation impacts that occur from delivery of the product cover direct exhaust emissions of fuel, environmental impacts of fuel production, as well as related infrastructure emissions. Environmental impacts from installation include waste packaging materials from wood pallet, cardboard box and plastic film. The impacts of energy consumption during installation are included, however used ancillary materials during installation are considered negligible.

## PRODUCT USE AND MAINTENANCE (B1-B7)

The product consume electricity during use phase and the scenario in this study is based on the Swedish electricity grid mix. Impacts due to electricity production include direct emissions to air, transformation and transmission losses. The product is most often used in office application areas with an annual operating of 2500 hours according to the European standard EN 15193-1. The reference service life is assumed to be 20 years.

**PRODUCT END OF LIFE (C1-C4, D)**

Consumption of energy are considered in the deconstruction process, but consumption of natural resources are assumed to be negligible. It is assumed that the waste is collected separately and transported to a waste treatment centre. Distance and transportation method to waste treatment is assumed to be 50 km with lorry. According to EN 50693:2019, the sequence of treatment operations occurring to the product shall include de-pollution, fractions separation and preparation, recycling, other material recovery, energy recovery and disposal. Energy and resource inputs for sorting and treating the waste streams for recycling and incineration with energy recovery are included.

Due to the material and energy recovery potential of parts in the lighting system, the end-of-life product is converted into recycled raw materials, or energy recovered from incineration that also displaces electricity and heat production. The rates of waste treatment for materials included in the product are based on statistics presented by agencies mainly in Scandinavia. Materials being recycled are 95 % of the metals, 74 % of the electrical and electronic waste and 10 % of the plastics. The wooden pallet used during transportation is also incinerated for energy recovery. The benefits and loads of incineration and recycling of the packaging materials are included.



# FLOW DIAGRAM



**DESIGN &  
PREPERATION**



**RAW MATERIAL &  
COMPONENTS**



**PRODUCTION**



**ASSEMBLY**



**PACKAGING &  
DELIVERY**



## LIFE-CYCLE ASSESSMENT

### CUT-OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

### ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways.

| Data type                      | Allocation                         |
|--------------------------------|------------------------------------|
| Raw materials                  | Partly allocated by mass or volume |
| Packaging materials            | Allocated by mass or volume        |
| Ancillary materials            | Not applicable                     |
| Manufacturing energy and waste | Allocated by mass or volume        |

### AVERAGES AND VARIABILITY

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Type of average                   | Multiple products                  |
| Averaging method                  | Averaged by shares of total volume |
| Variation in GWP-fossil for A1-A3 | -6 % / +2 %                        |

This is an average EPD of Notor 36 recessed from the manufacturer Fagerhults Belysning AB. The average EPD includes the length 1200 mm only, with Beta Opti louvre and Opal louvre. Notor 36 recessed Beta Opti with single installation is the representative product based on sales. The application area for the models are the same, as well as the reference service life time. Notor 36 recessed Opal with continuous installation represents a best case and Notor 36 recessed Beta Opti with start installation represents a worst case. The difference between representative case and best case is -6 %, and the difference between average case to worst case is +2 % in GWP fossil for A1-A3.

### LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. The EPD Generator uses Ecoinvent v3.8, Plastics Europe, Federal LCA Commons and One Click LCA databases as sources of environmental data.

# ENVIRONMENTAL IMPACT DATA

## CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

| Impact category                     | Unit                   | A1       | A2       | A3        | A1-A3     | A4       | A5       | B1  | B2  | B3  | B4  | B5  | B6       | B7  | C1       | C2       | C3       | C4       | D         |
|-------------------------------------|------------------------|----------|----------|-----------|-----------|----------|----------|-----|-----|-----|-----|-----|----------|-----|----------|----------|----------|----------|-----------|
| GWP – total <sup>1)</sup>           | kg CO <sub>2</sub> e   | 2,07E+01 | 5,57E-02 | 4,80E-01  | 2,13E+01  | 0,00E+00 | 7,21E-01 | MND | MND | MND | MND | MND | 5,45E+01 | MND | 2,23E-03 | 9,49E-03 | 4,94E-01 | 7,43E-03 | -5,67E+00 |
| GWP – fossil                        | kg CO <sub>2</sub> e   | 2,06E+01 | 5,57E-02 | 7,71E-01  | 2,14E+01  | 0,00E+00 | 3,53E-02 | MND | MND | MND | MND | MND | 5,09E+01 | MND | 2,07E-03 | 9,49E-03 | 4,94E-01 | 7,43E-03 | -5,43E+00 |
| GWP – biogenic                      | kg CO <sub>2</sub> e   | 0,00E+00 | 3,03E-06 | -6,86E-01 | -6,86E-01 | 0,00E+00 | 6,86E-01 | MND | MND | MND | MND | MND | 0,00E+00 | MND | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | -2,43E-01 |
| GWP – LULUC                         | kg CO <sub>2</sub> e   | 1,29E-01 | 1,81E-05 | 3,95E-01  | 5,25E-01  | 0,00E+00 | 1,58E-04 | MND | MND | MND | MND | MND | 3,57E+00 | MND | 1,54E-04 | 3,50E-06 | 7,64E-05 | 9,61E-07 | -1,73E-03 |
| Ozone depletion pot.                | kg CFC <sub>11</sub> e | 1,66E-06 | 1,26E-08 | 1,55E-07  | 1,83E-06  | 0,00E+00 | 8,19E-10 | MND | MND | MND | MND | MND | 2,48E-06 | MND | 9,63E-11 | 2,18E-09 | 4,96E-09 | 3,22E-10 | -3,98E-07 |
| Acidification potential             | mol H <sup>+</sup> e   | 2,46E-01 | 3,77E-04 | 1,30E-02  | 2,59E-01  | 0,00E+00 | 6,67E-05 | MND | MND | MND | MND | MND | 3,55E-01 | MND | 1,05E-05 | 4,02E-05 | 5,76E-04 | 8,53E-06 | -2,45E-02 |
| EP-freshwater <sup>2)</sup>         | kg Pe                  | 2,89E-03 | 3,46E-07 | 5,21E-05  | 2,94E-03  | 0,00E+00 | 2,66E-07 | MND | MND | MND | MND | MND | 2,77E-03 | MND | 9,74E-08 | 7,77E-08 | 2,70E-06 | 1,92E-08 | -2,37E-04 |
| EP-marine                           | kg Ne                  | 2,53E-02 | 1,09E-04 | 3,84E-03  | 2,92E-02  | 0,00E+00 | 2,50E-05 | MND | MND | MND | MND | MND | 6,07E-02 | MND | 2,36E-06 | 1,19E-05 | 1,42E-04 | 1,62E-05 | -4,79E-03 |
| EP-terrestrial                      | mol Ne                 | 3,02E-01 | 1,21E-03 | 5,76E-02  | 3,61E-01  | 0,00E+00 | 2,63E-04 | MND | MND | MND | MND | MND | 7,64E-01 | MND | 2,93E-05 | 1,32E-04 | 1,59E-03 | 3,22E-05 | -5,53E-02 |
| POCP (“smog”) <sup>3)</sup>         | kg NMVOCe              | 8,85E-02 | 3,45E-04 | 1,05E-02  | 9,94E-02  | 0,00E+00 | 6,73E-05 | MND | MND | MND | MND | MND | 1,80E-01 | MND | 6,70E-06 | 4,21E-05 | 4,19E-04 | 1,07E-05 | -2,32E-02 |
| ADP-minerals & metals <sup>4)</sup> | kg Sbe                 | 5,87E-03 | 9,85E-08 | 6,49E-06  | 5,87E-03  | 0,00E+00 | 1,06E-07 | MND | MND | MND | MND | MND | 3,49E-03 | MND | 3,88E-08 | 2,22E-08 | 4,37E-06 | 2,95E-09 | -7,46E-05 |
| ADP-fossil resources                | MJ                     | 2,75E+02 | 8,09E-01 | 1,05E+01  | 2,87E+02  | 0,00E+00 | 3,74E-01 | MND | MND | MND | MND | MND | 6,90E+03 | MND | 2,96E-01 | 1,42E-01 | 7,13E-01 | 2,33E-02 | -7,85E+01 |
| Water use <sup>5)</sup>             | m <sup>3</sup> e depr. | 9,31E+00 | 2,98E-03 | 1,31E+01  | 2,24E+01  | 0,00E+00 | 2,47E-02 | MND | MND | MND | MND | MND | 2,64E+02 | MND | 1,13E-02 | 6,38E-04 | 2,48E-02 | 1,09E-04 | -1,67E+00 |

1) GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO<sub>4</sub>e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.



**ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF**

| Impact category                  | Unit      | A1       | A2       | A3       | A1-A3    | A4       | A5       | B1  | B2  | B3  | B4  | B5  | B6       | B7  | C1       | C2       | C3       | C4       | D         |
|----------------------------------|-----------|----------|----------|----------|----------|----------|----------|-----|-----|-----|-----|-----|----------|-----|----------|----------|----------|----------|-----------|
| Particulate matter               | Incidence | 1,36E-06 | 4,66E-09 | 1,78E-07 | 1,54E-06 | 0,00E+00 | 8,72E-10 | MND | MND | MND | MND | MND | 4,23E-06 | MND | 1,54E-10 | 1,09E-09 | 6,25E-09 | 1,68E-10 | -4,30E-07 |
| Ionizing radiation <sup>6)</sup> | kBq U235e | 2,41E+00 | 3,81E-03 | 7,78E-02 | 2,49E+00 | 0,00E+00 | 2,18E-02 | MND | MND | MND | MND | MND | 4,93E+02 | MND | 2,13E-02 | 6,79E-04 | 7,33E-03 | 1,10E-04 | -2,89E-01 |
| Ecotoxicity (freshwater)         | CTUe      | 2,22E+03 | 6,48E-01 | 1,16E+02 | 2,33E+03 | 0,00E+00 | 3,38E-01 | MND | MND | MND | MND | MND | 3,41E+03 | MND | 1,04E-01 | 1,28E-01 | 3,93E+00 | 6,56E-02 | -1,39E+02 |
| Human toxicity, cancer           | CTUh      | 5,56E-03 | 1,65E-11 | 2,11E-09 | 5,56E-03 | 0,00E+00 | 2,20E-11 | MND | MND | MND | MND | MND | 1,14E-07 | MND | 2,70E-12 | 3,15E-12 | 1,13E-10 | 8,00E-13 | -4,11E-08 |
| Human tox. non-cancer            | CTUh      | 1,46E-02 | 6,90E-10 | 5,05E-08 | 1,46E-02 | 0,00E+00 | 6,39E-10 | MND | MND | MND | MND | MND | 2,68E-06 | MND | 5,30E-11 | 1,27E-10 | 1,01E-08 | 2,57E-11 | -6,61E-07 |
| SQP <sup>7)</sup>                | -         | 1,18E+02 | 6,91E-01 | 2,57E+02 | 3,76E+02 | 0,00E+00 | 1,23E-01 | MND | MND | MND | MND | MND | 1,61E+03 | MND | 6,71E-02 | 1,64E-01 | 9,21E-01 | 5,34E-02 | -3,72E+01 |

6) EN 15804+A2 disclaimer for Ionizing radiation, human health. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator; 7) SQP = Land use related impacts/soil quality.

**USE OF NATURAL RESOURCES**

| Impact category                    | Unit           | A1       | A2       | A3       | A1-A3    | A4       | A5        | B1  | B2  | B3  | B4  | B5  | B6       | B7  | C1       | C2       | C3        | C4        | D         |
|------------------------------------|----------------|----------|----------|----------|----------|----------|-----------|-----|-----|-----|-----|-----|----------|-----|----------|----------|-----------|-----------|-----------|
| Renew. PER as energy <sup>8)</sup> | MJ             | 5,53E+01 | 7,36E-03 | 9,56E+01 | 1,51E+02 | 0,00E+00 | 1,26E-01  | MND | MND | MND | MND | MND | 2,86E+03 | MND | 1,22E-01 | 1,61E-03 | 1,05E-01  | 3,47E-04  | -7,63E+00 |
| Renew. PER as material             | MJ             | 0,00E+00 | 0,00E+00 | 5,97E+00 | 5,97E+00 | 0,00E+00 | -5,97E+00 | MND | MND | MND | MND | MND | 0,00E+00 | MND | 0,00E+00 | 0,00E+00 | 0,00E+00  | 0,00E+00  | -2,57E+00 |
| Total use of renew. PER            | MJ             | 5,53E+01 | 7,36E-03 | 1,02E+02 | 1,57E+02 | 0,00E+00 | -5,85E+00 | MND | MND | MND | MND | MND | 2,86E+03 | MND | 1,22E-01 | 1,61E-03 | 1,05E-01  | 3,47E-04  | -1,02E+01 |
| Non-re. PER as energy              | MJ             | 2,71E+02 | 8,09E-01 | 9,85E+00 | 2,81E+02 | 0,00E+00 | 3,73E-01  | MND | MND | MND | MND | MND | 6,87E+03 | MND | 2,95E-01 | 1,43E-01 | 7,13E-01  | 2,33E-02  | -6,26E+01 |
| Non-re. PER as material            | MJ             | 2,16E+00 | 0,00E+00 | 6,44E-01 | 2,81E+00 | 0,00E+00 | -6,44E-01 | MND | MND | MND | MND | MND | 0,00E+00 | MND | 0,00E+00 | 0,00E+00 | -2,10E+00 | -6,48E-02 | 3,26E+00  |
| Total use of non-re. PER           | MJ             | 2,73E+02 | 8,09E-01 | 1,05E+01 | 2,84E+02 | 0,00E+00 | -2,71E-01 | MND | MND | MND | MND | MND | 6,87E+03 | MND | 2,95E-01 | 1,43E-01 | -1,38E+00 | -4,15E-02 | -5,94E+01 |
| Secondary materials                | kg             | 1,67E+00 | 1,93E-04 | 1,93E-01 | 1,87E+00 | 0,00E+00 | 1,67E-04  | MND | MND | MND | MND | MND | 6,23E-01 | MND | 2,05E-05 | 3,96E-05 | 5,95E-04  | 6,85E-06  | -1,48E+00 |
| Renew. secondary fuels             | MJ             | 8,14E-03 | 1,78E-06 | 1,39E-01 | 1,47E-01 | 0,00E+00 | 7,00E-07  | MND | MND | MND | MND | MND | 2,58E-03 | MND | 6,82E-08 | 3,99E-07 | 3,52E-05  | 1,38E-07  | -7,07E-04 |
| Non-ren. secondary fuels           | MJ             | 2,37E-05 | 0,00E+00 | 0,00E+00 | 2,37E-05 | 0,00E+00 | 0,00E+00  | MND | MND | MND | MND | MND | 0,00E+00 | MND | 0,00E+00 | 0,00E+00 | 0,00E+00  | 0,00E+00  | 0,00E+00  |
| Use of net fresh water             | m <sup>3</sup> | 3,54E-01 | 8,43E-05 | 3,00E-01 | 6,54E-01 | 0,00E+00 | 2,87E-04  | MND | MND | MND | MND | MND | 6,66E+00 | MND | 2,84E-04 | 1,85E-05 | 5,53E-04  | 2,53E-05  | -3,35E-02 |

8) PER = Primary energy resources.

**END OF LIFE – WASTE**

| Impact category     | Unit | A1       | A2       | A3       | A1-A3    | A4       | A5       | B1  | B2  | B3  | B4  | B5  | B6       | B7  | C1       | C2       | C3       | C4       | D         |
|---------------------|------|----------|----------|----------|----------|----------|----------|-----|-----|-----|-----|-----|----------|-----|----------|----------|----------|----------|-----------|
| Hazardous waste     | kg   | 2,63E+00 | 8,88E-04 | 4,07E-02 | 2,67E+00 | 0,00E+00 | 1,55E-03 | MND | MND | MND | MND | MND | 5,74E+00 | MND | 2,21E-04 | 1,89E-04 | 4,50E-03 | 0,00E+00 | -1,95E+00 |
| Non-hazardous waste | kg   | 7,01E+01 | 1,38E-02 | 8,14E-01 | 7,09E+01 | 0,00E+00 | 1,75E-01 | MND | MND | MND | MND | MND | 1,55E+02 | MND | 5,30E-03 | 3,10E-03 | 2,77E-01 | 1,25E-01 | -1,03E+01 |
| Radioactive waste   | kg   | 8,90E-04 | 5,54E-06 | 5,35E-05 | 9,49E-04 | 0,00E+00 | 4,85E-06 | MND | MND | MND | MND | MND | 1,06E-01 | MND | 4,56E-06 | 9,53E-07 | 3,15E-06 | 0,00E+00 | -1,57E-04 |

**END OF LIFE – OUTPUT FLOWS**

| Impact category          | Unit | A1       | A2       | A3       | A1-A3    | A4       | A5       | B1  | B2  | B3  | B4  | B5  | B6       | B7  | C1       | C2       | C3       | C4       | D        |
|--------------------------|------|----------|----------|----------|----------|----------|----------|-----|-----|-----|-----|-----|----------|-----|----------|----------|----------|----------|----------|
| Components for re-use    | kg   | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | MND | MND | MND | MND | MND | 0,00E+00 | MND | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| Materials for recycling  | kg   | 1,34E+00 | 0,00E+00 | 4,44E-01 | 1,79E+00 | 0,00E+00 | 1,50E-01 | MND | MND | MND | MND | MND | 0,00E+00 | MND | 0,00E+00 | 0,00E+00 | 1,75E+00 | 0,00E+00 | 0,00E+00 |
| Materials for energy rec | kg   | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 1,84E-01 | MND | MND | MND | MND | MND | 0,00E+00 | MND | 0,00E+00 | 0,00E+00 | 1,45E-01 | 0,00E+00 | 0,00E+00 |
| Exported energy          | MJ   | 7,80E-04 | 0,00E+00 | 0,00E+00 | 7,80E-04 | 0,00E+00 | 2,22E+00 | MND | MND | MND | MND | MND | 0,00E+00 | MND | 0,00E+00 | 0,00E+00 | 1,84E+00 | 0,00E+00 | 0,00E+00 |

**ENVIRONMENTAL IMPACTS – EN 15804+A1, CML / ISO 21930**

| Impact category      | Unit                               | A1       | A2       | A3       | A1-A3    | A4       | A5       | B1  | B2  | B3  | B4  | B5  | B6       | B7  | C1       | C2       | C3       | C4       | D         |
|----------------------|------------------------------------|----------|----------|----------|----------|----------|----------|-----|-----|-----|-----|-----|----------|-----|----------|----------|----------|----------|-----------|
| Global Warming Pot.  | kg CO <sub>2</sub> e               | 1,74E+01 | 7,26E-02 | 1,22E+00 | 1,87E+01 | 0,00E+00 | 3,64E-02 | MND | MND | MND | MND | MND | 5,38E+01 | MND | 2,20E-03 | 9,39E-03 | 4,93E-01 | 6,14E-03 | -5,19E+00 |
| Ozone depletion Pot. | kg CFC <sub>11</sub> e             | 6,75E-07 | 1,32E-08 | 1,43E-07 | 8,32E-07 | 0,00E+00 | 6,87E-10 | MND | MND | MND | MND | MND | 2,23E-06 | MND | 8,64E-11 | 1,73E-09 | 4,06E-09 | 2,55E-10 | -3,52E-07 |
| Acidification        | kg SO <sub>2</sub> e               | 1,91E-01 | 3,52E-04 | 8,53E-03 | 2,00E-01 | 0,00E+00 | 4,94E-05 | MND | MND | MND | MND | MND | 2,85E-01 | MND | 8,08E-06 | 3,12E-05 | 4,57E-04 | 6,44E-06 | -1,94E-02 |
| Eutrophication       | kg PO <sub>4</sub> <sup>3</sup> e  | 5,31E-02 | 6,47E-05 | 3,29E-03 | 5,65E-02 | 0,00E+00 | 5,11E-05 | MND | MND | MND | MND | MND | 1,43E-01 | MND | 4,83E-06 | 7,11E-06 | 1,99E-04 | 1,28E-03 | -9,99E-03 |
| POCP ("smog")        | kg C <sub>2</sub> H <sub>4</sub> e | 9,01E-03 | 1,12E-05 | 5,86E-04 | 9,61E-03 | 0,00E+00 | 2,83E-06 | MND | MND | MND | MND | MND | 1,38E-02 | MND | 4,23E-07 | 1,22E-06 | 1,63E-05 | 1,11E-06 | -2,38E-03 |
| ADP-elements         | kg Sbe                             | 3,64E-03 | 1,35E-07 | 6,22E-06 | 3,65E-03 | 0,00E+00 | 1,04E-07 | MND | MND | MND | MND | MND | 3,50E-03 | MND | 3,92E-08 | 2,15E-08 | 4,36E-06 | 2,88E-09 | -7,42E-05 |
| ADP-fossil           | MJ                                 | 2,27E+02 | 1,07E+00 | 1,05E+01 | 2,38E+02 | 0,00E+00 | 3,73E-01 | MND | MND | MND | MND | MND | 6,87E+03 | MND | 2,95E-01 | 1,42E-01 | 7,13E-01 | 2,33E-02 | -7,85E+01 |

## VERIFICATION STATEMENT

### VERIFICATION PROCESS FOR THIS EPD

This EPD has been verified in accordance with ISO 14025 by an independent, third-party verifier by reviewing results, documents and compliance with reference standard, ISO 14025 and ISO 14040/14044, following the process and checklists of the program operator for:

- This Environmental Product Declaration
- The Life-Cycle Assessment used in this EPD
- The digital background data for this EPD

Why does verification transparency matter? [Read more online](#)

This EPD has been generated by One Click LCA EPD generator, which has been verified and approved by the EPD Hub.

### THIRD-PARTY VERIFICATION STATEMENT

I hereby confirm that, following detailed examination, I have not established any relevant deviations by the studied Environmental Product Declaration (EPD), its LCA and project report, in terms of the data collected and used in the LCA calculations, the way the LCA-based calculations have been carried out, the presentation of environmental data in the EPD, and other additional environmental information, as present with respect to the procedural and methodological requirements in ISO 14025:2010 and reference standard.

I confirm that the company-specific data has been examined as regards plausibility and consistency; the declaration owner is responsible for its factual integrity and legal compliance.

I confirm that I have sufficient knowledge and experience of construction products, this specific product category, the construction industry, relevant standards, and the geographical area of the EPD to carry out this verification.

I confirm my independence in my role as verifier; I have not been involved in the execution of the LCA or in the development of the declaration and have no conflicts of interest regarding this verification.

Imane Uald lamkaddam, as an authorized verifier acting for EPD Hub Limited

30.05.2024

